

STUFFING BOX PACKING

TYPE	APPLICATION	DESCRIPTION	PART NO.
Standard Nitrile / Buna	Standard service Low pressure 200 Deg C	Available in either BLACK , RED or BLUE (Colours are only used to distinguish between packings, properties and application are the same)	A91SN-BLA A91SN-BLU A91SN-RED
Graphite	Standard service Low pressure 200 Deg C	Impregnated with graphite lubricant	A91SN-GRA
Solid Nitrile / Buna	Standard service High pressure 200 Deg C	90 Durometer nitrile	A91SN-SOL
Urethane	High pressure Low temperature use Good wear resistance	Solid Urethane	A91UR-SOL
Viton	High temperature 400 Deg C Chemical resistance	Solid Viton	A91VI-SOL
Solid Nitrile Crown	High & low pressure 200 Deg C	Fabric seal	A91SN-CWN
Solid HSN / HNBR	Sour service Up to 250 Deg C Good wear resistance	HSN / HNBR provides better chemical resistance and thermal stability	A91HS-BLA
HSN Crown	Sour service Up to 250 Deg C Good wear resistance	As above with a fabric seal	A91HS-CWN
Packing Puller	Removing packings	Screw type extractor for safely and easily removing packing from the stuffing box	A91PULLER

